


**Part Number:** 115162

**Part Description:** Compressed Natural Gas (CNG) Fuel Storage Cylinder



## Product Technical Specifications

### General Specifications

Internal Volume .....	139 ±2.1 Gallons (528 ±8 L)
Overall Length @ 350 psi .....	80.0" ±0.4" (2031 ±9mm)
Overall Diameter @ 350 psi .....	25" ±0.4" (637 ±9mm)
Cylinder Mass .....	215.8 ±11 lb (97.9 ±5 kg)
Approved Service Gas .....	Compressed Natural Gas (CNG)
Service Life .....	20 Years
Cylinder Construction .....	Type IV
Cylinder Certifications .....	NGV2-2007
Service Pressure .....	3600 psi (24.8 MPa) @ 70°F (21°C)
Minimum Working Pressure .....	290 psi (2 MPa)
Cylinder Temperature Range .....	-40°F (-40°C) to 185°F (85°C)
Color .....	Black

For Gasoline Gallon Equivalent (GGE), Diesel Gallon Equivalent (DGE) and Standard Cubic Feet (SCF) information for this cylinder refer to the *Quantum CNG Cylinder General Specifications* document.

### Approved Valves and Pressure Relief Devices (PRD)



Only approved valves and PRD's are to be installed in your Quantum cylinder. Installation of a valve, PRD, or combination of the two components not approved for your cylinder will result in death or serious injury.

#### Manual Valves:

1. Quantum PN 114816, Use with PRD #1

#### Automatic Valves:

None Approved

#### PRD's

1. Quantum PN 114962 PRD Manifold Assembly  
This PRD is only approved for use with manual valve #1 indicated above.



The PRD manifold assemblies indicated above MUST be built and installed using the specifications and criteria defined on the PRD manifold assembly data sheet for the cylinder and valve combination being used.

The PRD manifold assembly MUST be properly secured, if the PRD manifold is not secured the PRD manifold assembly may not operate as intended during a PRD event. Failure of the PRD manifold to operate as intended will result in death or serious injury.

**Mechanical Interface**

Valve Interface .....	1 1/8" -12 UNF-2B
Valve Boss Material .....	Anodized Aluminum
Second Valve Interface (if applicable) .....	N/A

**Torque Specifications**

Valve Interface (Recommended) .....	100 Ft. lb. (135 N.m.)
Second Valve Interface (if applicable) .....	N/A

**Maintenance Parts**

Valve Interface O-Ring .....	Quantum PN 111409-216
PRD (114962 Manifold Assembly) .....	Quantum PN 114056
Replacement Certification Label .....	Contact Quantum Technologies
Replacement Warning Label .....	Quantum PN 113224

**Cylinder Brackets**

Some jurisdictions require that cylinder manufacturer approved cylinder brackets be used for installation of cylinders. Use only cylinder brackets produced or approved by Quantum Technologies for mounting your CNG.

Use only cylinder brackets produced or approved by Quantum Technologies for mounting your CNG cylinder.

Selection and use of cylinder brackets is the sole responsibility of the installer to ensure the bracket selected will comply with all regulations applicable in the jurisdiction where the vehicle will be operated.

**Maintenance Considerations**

Inspect the CNG cylinder and brackets every 3 years or 36,000 miles (60,000 km), whichever comes first. The frequency and level of inspection may vary based on state and local requirements.

For additional information, refer to the *Type 4 Compressed Natural Gas (CNG) Cylinder Installation and Maintenance Guide* available at [www.qtw.com](http://www.qtw.com).